

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 8133  
Print date: 21.08.2025  
Version: 57

Wood Brightener Power-Gel  
Revision date: 20.05.2025  
Issue date: 20.05.2025

112116 EN  
Page 1 / 8

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

Article No. (manufacturer/supplier) 8133  
Trade name/designation Wood Brightener Power-Gel  
UFI: 0T10-T09X-800C-Q1XW

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Relevant identified uses**

Care-Product

**1.3. Details of the supplier of the safety data sheet**

**manufacturer**

Saicos Colour GmbH  
Carl-Zeiss-Str.3  
D-48336 Sassenberg

Telephone: +49 (0) 2583 3037-0  
Telefax: +49 (0) 2583 3037-10

**Department responsible for information:**

E-mail (competent person) info@saicos.de

**1.4. Emergency telephone number**

Giftnotruf Berlin: +49 30 30686 700 Beratung in Deutsch und Englisch

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].

Skin Corr. 1 / H314

Skin corrosion/irritation

Causes severe skin burns and eye damage.

Eye Dam. 1 / H318

Serious eye damage/eye irritation

Causes serious eye damage.

**2.2. Label elements**

**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

**Hazard pictograms**



**Danger**

**Hazard statements**

H314 Causes severe skin burns and eye damage.

**Precautionary statements**

P260 Do not breathe vapour.

P264 Wash hands thoroughly after handling.

P280 Wear protective gloves and eye protection/face protection.

P301 + P330 + P331 IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor/ physician.

P363 Wash contaminated clothing before reuse.

P405 Keep locked up.

P501 Dispose of contents/container to industrial incineration plant.

**Hazard components for labelling**

oxalic acid

**Supplemental hazard information**

not applicable

**2.3. Other hazards**

No information available.

**SECTION 3: Composition/information on ingredients**

**3.2. Mixtures**

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 8133  
Print date: 21.08.2025  
Version: 57

Wood Brightener Power-Gel  
Revision date: 20.05.2025  
Issue date: 20.05.2025

112116 EN  
Page 2 / 8

**Description** Cleaning agent, acidic

**Classification according to Regulation (EC) No 1272/2008 [CLP]**

EC No.	REACH No.	weight-%
CAS No.	Designation	
Index No.	classification // Remark	
205-634-3	01-2119534576-33	
144-62-7	oxalic acid	2,5 - 5
607-006-00-8	Acute Tox. 4 H302 / Acute Tox. 4 H312 / Skin Corr. 1 H314 / Eye Dam. 1 H318 / Met. Corr. 1 H290 Acute toxicity estimate (ATE): ATE (oral): 375 mg/kg bw	

**Additional information**

Full text of classification: see section 16

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

**In case of inhalation**

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

**Following skin contact**

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

**After eye contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**Following ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

**4.3. Indication of any immediate medical attention and special treatment needed**

First Aid, decontamination, treatment of symptoms.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

**Unsuitable extinguishing media**

strong water jet

**5.2. Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

**5.3. Advice for firefighters**

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways.

**SECTION 6: Accidental release measures**

**6.1. Personal precautions, protective equipment and emergency procedures**

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

**6.3. Methods and material for containment and cleaning up**

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 8133  
Print date: 21.08.2025  
Version: 57

Wood Brightener Power-Gel  
Revision date: 20.05.2025  
Issue date: 20.05.2025

112116 EN  
Page 3 / 8

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13). Clean using cleansing agents. Do not use solvents.

#### 6.4. Reference to other sections

Observe protective provisions (see section 7 and 8).

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

##### Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

##### Further information

Vapours are heavier than air. Vapours form explosive mixtures with air.

#### 7.2. Conditions for safe storage, including any incompatibilities

##### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (TRGS 727)".

##### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

##### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 30 °C. Protect from heat and direct sunlight.

Due to the content of organic solvents in the preparation:

Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

#### 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### Occupational exposure limit values:

oxalic acid

Index No. 607-006-00-8 / EC No. 205-634-3 / CAS No. 144-62-7

WEL, TWA: 1 mg/m<sup>3</sup>

WEL, STEL: 2 mg/m<sup>3</sup>

##### Additional information

TWA : Long-term occupational exposure limit value

STEL : short-term occupational exposure limit value

Ceiling : peak limitation

##### DNEL:

oxalic acid

Index No. 607-006-00-8 / EC No. 205-634-3 / CAS No. 144-62-7

DNEL acute dermal, short-term (local), Workers: 0,69 mg/cm<sup>2</sup>

DNEL long-term dermal (systemic), Workers: 2,29 mg/kg

DNEL long-term inhalative (systemic), Workers: 4,03 mg/m<sup>3</sup>

DNEL long-term oral (repeated), Consumer: 1,14 mg/kg bw/day

DNEL acute dermal, short-term (local), Consumer: 0,35 mg/cm<sup>2</sup>

DNEL long-term dermal (systemic), Consumer: 1,14 mg/kg bw/day

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 8133  
Print date: 21.08.2025  
Version: 57

Wood Brightener Power-Gel  
Revision date: 20.05.2025  
Issue date: 20.05.2025

112116 EN  
Page 4 / 8

## **PNEC:**

oxalic acid  
Index No. 607-006-00-8 / EC No. 205-634-3 / CAS No. 144-62-7  
PNEC aquatic, freshwater: 0,1622 mg/L  
PNEC aquatic, marine water: 0,0162 mg/L  
PNEC aquatic, intermittent release: 1,622 mg/L  
PNEC sewage treatment plant (STP): 1550 mg/L

## **8.2. Exposure controls**

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

### **Personal protection equipment**

#### **Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used.

#### **Hand protection**

For prolonged or repeated handling the following glove material must be used: Butyl caoutchouc (butyl rubber)

Thickness of the glove material > 0,4 mm ; Breakthrough time: > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### **Eye/face protection**

Wear closely fitting protective glasses in case of splashes.

#### **Body protection**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

#### **Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

### **Environmental exposure controls**

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

## **SECTION 9: Physical and chemical properties**

### **9.1. Information on basic physical and chemical properties**

<b>Physical state:</b>	<b>Liquid</b>
<b>Colour:</b>	<b>Colour</b>
<b>Odour:</b>	<b>characteristic</b>
<b>Odour threshold:</b>	<b>not applicable</b>
<b>Melting point/freezing point:</b>	<b>not applicable</b>
<b>Initial boiling point and boiling range:</b>	<b>100 °C</b> Source: water
<b>Flammability</b>	not applicable
<b>Lower and upper explosion limit:</b>	
<b>Lower explosion limit:</b>	<b>not applicable</b>
<b>Upper explosion limit:</b>	<b>not applicable</b>
<b>Flash point:</b>	<b>not applicable</b>
<b>Auto-ignition temperature:</b>	<b>not applicable</b>
<b>Decomposition temperature:</b>	<b>not applicable</b>
<b>pH at 20 °C:</b>	<b>1 - 2 / 100,0 weight-%</b>
<b>Kinematic viscosity (40°C):</b>	<b>0,94 mm<sup>2</sup>/s</b>
<b>Viscosity at 20 °C:</b>	<b>0,95 mPa* s</b>
<b>Solubility(ies):</b>	
<b>Water solubility at 20 °C:</b>	<b>completely miscible</b>

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 8133  
Print date: 21.08.2025  
Version: 57

Wood Brightener Power-Gel  
Revision date: 20.05.2025  
Issue date: 20.05.2025

112116 EN  
Page 5 / 8

**Partition coefficient: n-octanol/water:** see section 12  
**Vapour pressure at 20 °C:** 21,47 mbar  
Method: calculated.

**Density and/or relative density:**  
**Density at 20 °C:** 1,02 g/cm<sup>3</sup>  
**Relative vapour density:** not applicable  
**particle characteristics:** not applicable

9.2. **Other information**

**Solid content:** 6 weight-%  
**solvent content:**  
**Organic solvents:** 0 weight-%  
**Water:** 93 weight-%

**SECTION 10: Stability and reactivity**

10.1. **Reactivity**

No information available.

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.

10.3. **Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. **Conditions to avoid**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7. Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials**

not applicable

10.6. **Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

**SECTION 11: Toxicological information**

11.1. **Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity**

oxalic acid

oral, LD50, Rat: 375 mg/kg

**Skin corrosion/irritation; Serious eye damage/eye irritation**

Causes severe skin burns and eye damage.

oxalic acid

Skin (4 h)

eyes

**Respiratory or skin sensitisation**

Based on available data, the classification criteria are not met.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Based on available data, the classification criteria are not met.

**STOT-single exposure; STOT-repeated exposure**

Based on available data, the classification criteria are not met.

**Aspiration hazard**

Based on available data, the classification criteria are not met.

**Practical experience/human evidence**

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the

# Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2020/878



Article No.: 8133  
Print date: 21.08.2025  
Version: 57

Wood Brightener Power-Gel  
Revision date: 20.05.2025  
Issue date: 20.05.2025

112116 EN  
Page 6 / 8

aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

## Overall assessment on CMR properties

The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

### 11.2. Information on other hazards

#### Endocrine disrupting properties

No information available.

## SECTION 12: Ecological information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Do not allow to enter into surface water or drains.

### 12.1. Toxicity

oxalic acid

Fish toxicity, LC50: 160 mg/L (96 h)

Daphnia toxicity, EC50, Daphnia magna (Big water flea): 160,2 mg/L (48 h)

#### Long-term Ecotoxicity

Toxicological data are not available.

### 12.2. Persistence and degradability

Toxicological data are not available.

### 12.3. Bioaccumulative potential

Toxicological data are not available.

#### Bioconcentration factor (BCF)

Toxicological data are not available.

### 12.4. Mobility in soil

Toxicological data are not available.

### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

### 12.6. Endocrine disrupting properties

No information available.

### 12.7. Other adverse effects

No information available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Appropriate disposal / Product Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

#### List of proposed waste codes/waste designations in accordance with EWC

080111\* Waste paint and varnish containing organic solvents or other dangerous substances

\*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

#### Appropriate disposal / Package Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

## SECTION 14: Transport information

### 14.1. UN number or ID number

UN 3265

### 14.2. UN proper shipping name

Land transport (ADR/RID):

Corrosive liquid, acidic, organic, n.o.s.

Sea transport (IMDG):

CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.

Air transport (ICAO-TI / IATA-DGR):

Corrosive liquid, acidic, organic, n.o.s.

### 14.3. Transport hazard class(es)

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) 2020/878**



Article No.: 8133 Wood Brightener Power-Gel  
 Print date: 21.08.2025 Revision date: 20.05.2025 112116 EN  
 Version: 57 Issue date: 20.05.2025 Page 7 / 8

- Land transport (ADR/RID): 8  
 Sea transport (IMDG) 8  
 Air transport (ICAO-TI / IATA-DGR)
- 14.4. Packing group** II
- 14.5. Environmental hazards**  
 Land transport (ADR/RID) not applicable  
 Marine pollutant not applicable
- 14.6. Special precautions for user**  
 Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.  
 Advices on safe handling: see parts 6 - 8
- Further information**
- Land transport (ADR/RID)**  
 Tunnel restriction code E
- Sea transport (IMDG)**  
 EmS-No. F-A, S-B
- 14.7. Maritime transport in bulk according to IMO instruments**  
 No transport as bulk according IBC - Code.

**SECTION 15: Regulatory information**

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**
- EU legislation**  
**Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive]**  
 VOC-value (in g/L): 3
- National regulations**  
**Restrictions of occupation**  
 Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.  
 Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

**15.2. Chemical Safety Assessment**  
**For the following substances of this mixture a chemical safety assessment has been carried out:**

EC No. CAS No.	Designation	REACH No.
205-634-3 144-62-7	oxalic acid	01-2119534576-33

**SECTION 16: Other information**

**Full text of classification in section 3:**

Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Skin Corr. 1 / H314	Skin corrosion/irritation	Causes severe skin burns and eye damage.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Met. Corr. 1 / H290	Corrosive to metals	May be corrosive to metals.

**Classification procedure**  
 Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Skin Corr. 1	Skin corrosion/irritation	Calculation method.
Eye Dam. 1	Serious eye damage/eye irritation	Calculation method.

**Abbreviations and acronyms**

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) 2020/878



Article No.: 8133  
Print date: 21.08.2025  
Version: 57

Wood Brightener Power-Gel  
Revision date: 20.05.2025  
Issue date: 20.05.2025

112116 EN  
Page 8 / 8

---

CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose
MAK	Maximum workplace concentration
MARPOL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

**Further information**

Classification according to Regulation (EC) No 1272/2008 [CLP]

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in section 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.